

# AE

{ - 20 { + 10 10 } }

{ - 20 { + 17 17 } }

{ - 20 { + 3 3 } }

# WAE

```
{with {x 10}  
  {- 20 {+ x x}}}}
```

```
{with {x 17}  
  {- 20 {+ x x}}}}
```

```
{with {x 3}  
  {- 20 {+ x x}}}}
```

# F1WAE

```
{def fun {f x}
  {- 20 {+ x x}}}
```

{f 10}

{f 17}

{f 3}

# F1WAE

```
{deffun {f x}           {f 10}
  {- 20 {twice x}}}}
                                     {f 17}
{deffun {twice y}
  {+ y y}}                          {f 3}
```

```
; interp : F1WAE list-of-FunDef -> num
```

# F1WAE

```
{deffun {f x}           {f 10}
  {- 20 {twice x}}}]
{deffun {twice y}
  {+ y y}]           {f 17}
{f 3}
```

$\langle \text{FunDef} \rangle ::= \{ \text{deffun } \{ \langle \text{id} \rangle \langle \text{id} \rangle \} \langle \text{F1WAE} \rangle \}$

# F1WAE

```
{deffun {f x}           {f 10}
  {- 20 {twice x}}}}
                                     {f 17}
{deffun {twice y}
  {+ y y}}                          {f 3}
```

```
<FunDef> ::= {deffun {<id> <id>} <F1WAE>}
<F1WAE>  ::= ...
          | {<id> <F1WAE>}
```

# F1WAE Grammar

**<FunDef>** ::= { deffun { <id> <id> } <F1WAE> }



**<F1WAE>** ::= <num>  
| { + <F1WAE> <F1WAE> }  
| { - <F1WAE> <F1WAE> }  
| { with { <id> <F1WAE> } <F1WAE> }  
| <id>  
| { <id> <F1WAE> }



# F1WAE Datatypes

```
(define-type FunDef
  [fundef (fun-name symbol?)
          (arg-name symbol?)
          (body F1WAE?)])
```

```
(define-type F1WAE
  [num (n number?)]
  [add (lhs F1WAE?)
       (rhs F1WAE?)])
...
[app (fun-name symbol?)
     (arg F1WAE?)])
```



# F1WAE Interp

```
(define (interp a-wae fundefs)
  (type-case F1WAE a-wae
    [num (n) n]
    [add (l r) (+ (interp l fundefs)
                  (interp r fundefs))]
    ...
    [app (name arg-expr)
         ...]))

(test (interp (add (num 1) (num 1))
              empty)
      2)
```

# F1WAE Interp

```
(define (interp a-wae fundefs)
  (type-case F1WAE a-wae
    [num (n) n]
    [add (l r) (+ (interp l fundefs)
                  (interp r fundefs))]
    ...
    [app (name arg-expr)
         ...]))
```

```
(test (interp (add (num 1) (num 1))
              (list
                (fundef 'f 'x
                        (add (id 'x) (num 3))))))
2)
```

# F1WAE Interp

```
(define (interp a-wae fundefs)
  (type-case F1WAE a-wae
    [num (n) n]
    [add (l r) (+ (interp l fundefs)
                  (interp r fundefs))]
    ...
    [app (name arg-expr)
         ...]))
```

```
(test (interp (app 'f (num 1))
              (list
                (fundef 'f 'x
                        (add (id 'x) (num 3)))))
  4)
```

# F1WAE Interp

```
(define (interp a-wae fundefs)
  (type-case F1WAE a-wae
    [num (n) n]
    [add (l r) (+ (interp l fundefs)
                  (interp r fundefs))]
    ...
    [app (name arg-expr)
         ...]))

(test (interp (app 'f (num 10))
              (list
                (fundef 'f 'x
                        (sub (num 20)
                             (app 'twice (id 'x))))
                (fundef 'twice 'y
                        (add (id 'y) (id 'y))))
      0))
```

# F1WAE Interp

```
(define (interp a-wae fundefs)
  (type-case F1WAE a-wae
    [num (n) n]
    [add (l r) (+ (interp l fundefs)
                  (interp r fundefs))]
    ...
    [app (name arg-expr)
         ... (interp arg-expr fundefs) ... ]))
```

# F1WAE Interp

```
(define (interp a-wae fundefs)
  (type-case F1WAE a-wae
    [num (n) n]
    [add (l r) (+ (interp l fundefs)
                  (interp r fundefs))]
    ...
    [app (name arg-expr)
         ... (lookup-fundef name fundefs)
         ... (interp arg-expr fundefs) ... ]))
```

```
; lookup-fundef : symbol list-of-FunDef -> FunDef
```

# F1WAE Interp

```
(define (interp a-wae fundefs)
  (type-case F1WAE a-wae
    [num (n) n]
    [add (l r) (+ (interp l fundefs)
                  (interp r fundefs))]
    ...
    [app (name arg-expr)
         (local [(define a-fundef
                   (lookup-fundef name fundefs))]
               (interp (subst (fundef-body a-fundef)
                              (fundef-arg-name a-fundef)
                              (interp arg-expr fundefs))
                        fundefs))]))))
```

# Lookup

```
; lookup-fundef : symbol list-of-FunDef -> FunDef  
(define (lookup-fundef name fundefs)  
  ...)
```



# Lookup

```
; lookup-fundef : symbol list-of-FunDef -> FunDef
(define (lookup-fundef name fundefs)
  (cond
    [(empty? fundefs)
     ...]
    [else
     ... (first fundefs)
     ... (lookup-fundef name (rest fundefs))
     ...])))
```

# Lookup

```
; lookup-fundef : symbol list-of-FunDef -> FunDef
(define (lookup-fundef name fundefs)
  (cond
    [(empty? fundefs)
     (error 'interp "unknown function")]
    [else
     (if (symbol=? name (fundef-fun-name
                        (first fundefs)))
         (first fundefs)
         (lookup-fundef name (rest fundefs))))]))
```