

Arithmetic Language

```
<AE> ::= <num>
      | { + <AE> <AE> }
      | { - <AE> <AE> }
```

```
(define-type AE
  [num (n number?)]
  [add (lhs AE?)
       (rhs AE?)]
  [sub (lhs AE?)
       (rhs AE?)])
```

Arithmetic Language

```
<AE> ::= <num>
      | {+ <AE> <AE>}
      | {- <AE> <AE>}
```

```
; interp AE -> num
(define (interp an-ae)
  (type-case AE an-ae
    [num (n) n]
    [add (l r) (+ (interp l) (interp r))]
    [sub (l r) (- (interp l) (interp r))]))
```

```
(test (interp (add (num 1) (add 2))) 3)
```

Arithmetic Language

```
<AE> ::= <num>
      | {+ <AE> <AE>}
      | {- <AE> <AE>}
```

```
; parse: s-expr -> AE
(define (parse input)
  (cond
    [(number? input) (num input)]
    [(eq? (first input) '+)
     (add (parse (second input))
          (parse (third input)))]
    [(eq? (first input) '-')
     (sub (parse (second input))
          (parse (third input)))]
    [else (error 'parse "bad syntax: ~a" input)]))

(test (interp (parse '{+ 1 2})) 3)
```

The Arbitrariness of Identifiers

Are the following two programs equivalent?

```
(define (f x) (+ x 1))  
(f 10)
```

```
(define (f y) (+ y 1))  
(f 10)
```

yes

argument is consistently renamed

The Arbitrariness of Identifiers

Are the following two programs equivalent?

```
(define (f x) (+ x 1))  
(f 10)
```

```
(define (f x) (+ y 1))  
(f 10)
```

no

not a use of the argument anymore

The Arbitrariness of Identifiers

Are the following two programs equivalent?

```
(define (f x) (+ x 1))  
(f 10)
```

```
(define (f y) (+ x 1))  
(f 10)
```

no

not a use of the argument anymore

The Arbitrariness of Identifiers

Are the following two programs equivalent?

```
(define (f x) (+ y 1))  
(f 10)
```

```
(define (f z) (+ y 1))  
(f 10)
```

yes

argument never used, so almost any name is ok

The Arbitrariness of Identifiers

Are the following two programs equivalent?

```
(define (f x) (+ y 1))  
(f 10)
```

```
(define (f y) (+ y 1))  
(f 10)
```

no

now a use of the argument

The Arbitrariness of Identifiers

Are the following two programs equivalent?

```
(define (f x) (+ y 1))  
(f 10)
```

```
(define (f x) (+ z 1))  
(f 10)
```

no

still an undefined identifier, but a different one

The Arbitrariness of Identifiers

Are the following two programs equivalent?

```
(define (f x)
  (local [(define y 10)]
    (+ x y)))
(f 0)

(define (f z)
  (local [(define y 10)]
    (+ z y)))
(f 0)
```

yes

argument is consistently renamed

The Arbitrariness of Identifiers

Are the following two programs equivalent?

```
(define (f x)
  (local [(define y 10)]
    (+ x y)))
(f 0)
```

```
(define (f x)
  (local [(define z 10)]
    (+ x z)))
(f 0)
```

yes

local identifier is consistently renamed

The Arbitrariness of Identifiers

Are the following two programs equivalent?

```
(define (f x)
  (local [(define y 10)]
    (+ x y)))
(f 0)
```

```
(define (f x)
  (local [(define x 10)]
    (+ x x)))
(f 0)
```

no

local identifier now hides the argument

The Arbitrariness of Identifiers

Are the following two programs equivalent?

```
(define (f x)
  (local [(define y 10)]
    (+ x y)))
(f 0)
```

```
(define (f y)
  (local [(define y 10)]
    (+ y y)))
(f 0)
```

no

local identifier now hides the argument

Free and Bound Identifiers

An identifier for the argument of a function or the name of a local identifier is a **binding occurrence**

```
(define (f x y) (+ x y z))
```

```
(local [(define a 3)
        (define c 4)]
  (+ a b c))
```

Free and Bound Identifiers

A use of a function argument or a local identifier is a **bound occurrence**

```
(define (f x y) (+ x y z))
```

```
(local [(define a 3)
        (define c 4)]
  (+ a b c))
```

Free and Bound Identifiers

A use of an identifier that is not function argument or a local identifier is a ***free identifier***

```
(define (f x y) (+ x y z))
```

```
(local [(define a 3)
        (define c 4)]
  (+ a b c))
```

Arithmetic Language

$$\begin{aligned} \langle \text{AE} \rangle & ::= \langle \text{num} \rangle \\ & | \{ + \langle \text{AE} \rangle \langle \text{AE} \rangle \} \\ & | \{ - \langle \text{AE} \rangle \langle \text{AE} \rangle \} \end{aligned}$$

No identifiers to help us study binding...

With Arithmetic Language

```
<WAE> ::= <num>
        | {+ <WAE> <WAE>}
        | {- <WAE> <WAE>}
        | {with {<id> <WAE>} <WAE>} 
        | <id> 
```

```
{with {x {+ 1 2}}
      {+ x x}}      => 6
```

With Arithmetic Language

```
<WAE> ::= <num>
        | {+ <WAE> <WAE>}
        | {- <WAE> <WAE>}
        | {with {<id> <WAE>} <WAE>} 
        | <id> 
```

x \Rightarrow *error: free identifier*

With Arithmetic Language

```
<WAE> ::= <num>
|      {+ <WAE> <WAE>}
|      {- <WAE> <WAE>}
|      {with {<id> <WAE>} <WAE>}
|      <id>
```

 

```
{+ {with {x {+ 1 2}}
    {+ x x}}
  {with {x {- 4 3}}
    {+ x x}}}} ⇒ 8
```

With Arithmetic Language

```
<WAE> ::= <num>
        | {+ <WAE> <WAE>}
        | {- <WAE> <WAE>}
        | {with {<id> <WAE>} <WAE>} 
        | <id> 
```

```
{+ {with {x {+ 1 2}}
      {+ x x}}
  {with {y {- 4 3}}
      {+ y y}}}} ⇒ 8
```

With Arithmetic Language

```
<WAE> ::= <num>
|      {+ <WAE> <WAE>}
|      {- <WAE> <WAE>}
|      {with {<id> <WAE>} <WAE>}
|      <id>
```

 

```
{with {x {+ 1 2}}
  {with {x {- 4 3}}
    {+ x x}}}} ⇒ 2
```

With Arithmetic Language

```
<WAE> ::= <num>
        | {+ <WAE> <WAE>}
        | {- <WAE> <WAE>}
        | {with {<id> <WAE>} <WAE>} 
        | <id> 
```

```
{with {x {+ 1 2}}
  {with {y {- 4 3}}
    {+ x x}}}} ⇒ 6
```

With Arithmetic Language

```
<WAE> ::= <num>
        | {+ <WAE> <WAE>}
        | {- <WAE> <WAE>}
        | {with {<id> <WAE>} <WAE>}
        | <id>
```

NEW

NEW

```
(define-type WAE
  [num (n number?)]
  [add (lhs WAE?)
        (rhs WAE?)]
  [sub (lhs WAE?)
        (rhs WAE?)]
  [with (name symbol?)
         (named-expr WAE?)
         (body WAE?)]
  [id (name symbol?)])
```

With Arithmetic Language

```
<WAE> ::= <num>
        | {+ <WAE> <WAE>}
        | {- <WAE> <WAE>}
        | {with {<id> <WAE>} <WAE>} 
        | <id> 
```

```
(define (interp a-wae)
  (type-case WAE a-wae
    [num (n) n]
    [add (l r) (+ (interp l) (interp r))]
    [sub (l r) (- (interp l) (interp r))]
    [with (bound-id named-expr body-expr)
     ...]
    [id (name) ...]))
```

With Arithmetic Language

```
<WAE> ::= <num>
        | {+ <WAE> <WAE>}
        | {- <WAE> <WAE>}
        | {with {<id> <WAE>} <WAE>}
        | <id>
```

 

```
(define (interp a-wae)
  (type-case WAE a-wae
    [num (n) n]
    [add (l r) (+ (interp l) (interp r))]
    [sub (l r) (- (interp l) (interp r))]
    [with (bound-id named-expr body-expr)
     ...]
    [id (name) (error 'interp "free variable")]))
```

With Arithmetic Language

```
<WAE> ::= <num>
        | {+ <WAE> <WAE>}
        | {- <WAE> <WAE>}
        | {with {<id> <WAE>} <WAE>}
        | <id>
```

 

```
(define (interp a-wae)
  (type-case WAE a-wae
    [num (n) n]
    [add (l r) (+ (interp l) (interp r))]
    [sub (l r) (- (interp l) (interp r))]
    [with (bound-id named-expr body-expr)
     ... (interp named-expr) ... ]
    [id (name) (error 'interp "free variable")]))
```

With Arithmetic Language

```
<WAE> ::= <num>
        | {+ <WAE> <WAE>}
        | {- <WAE> <WAE>}
        | {with {<id> <WAE>} <WAE>} 
        | <id> 
```

```
(define (interp a-wae)
  (type-case WAE a-wae
    [num (n) n]
    [add (l r) (+ (interp l) (interp r))]
    [sub (l r) (- (interp l) (interp r))]
    [with (bound-id named-expr body-expr)
     ... (interp named-expr)
     ... (interp body-expr) ... ]
    [id (name) (error 'interp "free variable")]))
```

With Arithmetic Language

```
<WAE> ::= <num>
        | {+ <WAE> <WAE>}
        | {- <WAE> <WAE>}
        | {with {<id> <WAE>} <WAE>} 
        | <id> 
```

```
(define (interp a-wae)
  (type-case WAE a-wae
    [num (n) n]
    [add (l r) (+ (interp l) (interp r))]
    [sub (l r) (- (interp l) (interp r))]
    [with (bound-id named-expr body-expr)
      (interp (subst body-expr
                    bound-id
                    (interp named-expr)))]
    [id (name) (error 'interp "free variable")]))
```

Substitution

```
; subst : WAE symbol num -> WAE
(define (subst a-wae sub-id val)
  (type-case WAE a-wae
    [num (n) ...]
    [add (l r) ...]
    [sub (l r) ...]
    [with (bound-id named-expr body-expr)
     ...]
    [id (name) ...])))
```

Let's make examples/tests first...

Example Substitutions

```
; 10 for x in {+ 1 x} ⇒ {+ 1 10}
(test (subst (add (num 1) (id 'x)) 'x 10)
      (add (num 1) (num 10)))
```

```
; 10 for x in x ⇒ 10
(test (subst (id 'x) 'x 10)
      (num 10))
```

```
; 10 for x in y ⇒ y
(test (subst (id 'y) 'x 10)
      (id 'y))
```

```
; 10 for y in {- x 1} ⇒ {- x 1}
(test (subst (sub (id 'x) (num 1)) 'y 10)
      (sub (id 'x) (num 1)))
```

Substitution

```
; subst : WAE symbol num -> WAE
(define (subst a-wae sub-id val)
  (type-case WAE a-wae
    [num (n) a-wae]
    [add (l r) (add (subst l sub-id val)
                    (subst r sub-id val))]
    [sub (l r) (sub (subst l sub-id val)
                    (subst r sub-id val))]
    [with (bound-id named-expr body-expr)
          ...]
    [id (name) (if (symbol=? name sub-id)
                   (num val)
                   a-wae))]))
```

Example Substitutions

```
; 10 for x in {with {y 17} x} ⇒ {with {y 17} 10}
(test (subst (with 'y (num 17) (id 'x)) 'x 10)
      (with 'y (num 17) (num 10)))
```

```
; 10 for x in {with {y x} y} ⇒ {with {y 10} y}
(test (subst (with 'y (id 'x) (id 'y)) 'x 10)
      (with 'y (num 10) (id 'y)))
```

```
; 10 for x in {with {x y} x} ⇒ {with {x y} x}
(test (subst (with 'x (id 'y) (id 'x)) 'x 10)
      (with 'x (id 'y) (id 'x)))
```

Substitution replaces

- free identifiers with the same name
- no binding identifiers
- no bound identifiers

Substitution

An identifier is bound when it appears in the body of a **with** binding the same name

Conversely, a free variable of a name appears in a **with** only if the **with** doesn't bind the name

```
; subst : WAE symbol num -> WAE
(define (subst a-wae sub-id val)
  (type-case WAE a-wae
    ...
    [with (bound-id named-expr body-expr)
      (with bound-id
        (subst named-expr sub-id val)
        (if (symbol=? bound-id sub-id)
            body-expr
            (subst body-expr sub-id val))))])
    ...))
```