

Shrinking the Language

- We've seen that **with** is not really necessary when we have **fun**...
- ... and **rec** is not really necessary when we have **fun**...
- ... and neither, it turns out, are fancy things like numbers, **+**, **-** or **if0**

This lecture's material won't show up on any homework or exam, but it may help you understand HW 4

LC Grammar

```
<LC> ::= <id>  
      | {<LC> <LC>}  
      | {fun {<id>} <LC>}
```

Implementing Programs with LC

Can you write a program that produces the identity function?

```
{ fun {x} x }
```

Implementing Programs with LC

Can you write a program that produces zero?

What's zero? I only know how to write functions!

Turing Machine programmer: What's a *function*? I only know how to write 0 or 1!

We need to encode zero — instead of agreeing to write zero as 0, let's agree to write it as

```
{fun {f} {fun {x} x}}
```

This encoding is the start of **Church numerals**...

Implementing Numbers with LC

Can you write a program that produces zero?

```
{ fun { f } { fun { x } x } }
```

... which is also the function that takes **f** and **x** and applies **f** to **x** zero times

From now on, we'll write **zero** as shorthand for the above expression:

```
zero  $\stackrel{\text{def}}{=}$  { fun { f } { fun { x } x } }
```

Implementing Numbers with LC

Can you write a program that produces one?

`one` $\stackrel{\text{def}}{=}$ `{ fun { f } { fun { x } { f x } } }`

... which is also the function that takes `f` and `x` and applies `f` to `x` one time

Implementing Numbers with LC

Can you write a program that produces two?

```
two def = {fun {f} {fun {x} {f {f x}}}}
```

... which is also the function that takes **f** and **x** and applies **f** to **x** two times

Implementing Booleans with LC

Can you write a program that produces true?

`true` $\stackrel{\text{def}}{=}$ `{ fun {x} { fun {y} x } }`

... which is also the function that takes two arguments and returns the first one

Implementing Booleans with LC

Can you write a program that produces false?

`false` ^{def} = `{fun {x} {fun {y} y}}`

... which is also the function that takes two arguments and returns the second one

Implementing Branches with LC

`true` $\stackrel{\text{def}}{=} \{\text{fun } \{x\} \{\text{fun } \{y\} x\}\}$

`false` $\stackrel{\text{def}}{=} \{\text{fun } \{x\} \{\text{fun } \{y\} y\}\}$

`zero` $\stackrel{\text{def}}{=} \{\text{fun } \{f\} \{\text{fun } \{x\} x\}\}$

`one` $\stackrel{\text{def}}{=} \{\text{fun } \{f\} \{\text{fun } \{x\} \{f x\}\}\}$

`two` $\stackrel{\text{def}}{=} \{\text{fun } \{f\} \{\text{fun } \{x\} \{f \{f x\}\}\}\}$

Can you write a program that produces zero when given true, one when given false?

`\{\text{fun } \{b\} \{\{b zero\} one\}\}`

... because `true` returns its first argument and `false` returns its second argument

`\{\{fun } \{b\} \{\{b zero\} one\}\} true\} \Rightarrow \{\{true zero\} one\}
 \Rightarrow zero`

`\{\{fun } \{b\} \{\{b zero\} one\}\} false\} \Rightarrow \{\{false zero\} one\}
 \Rightarrow one`

Implementing Pairs

Can you write a program that takes two arguments and produces a pair?

```
cons def = {fun {x} {fun {y}
              {fun {b} {{b x} y}}}}
```

Examples:

```
{{cons zero} one} ⇒ {fun {b} {{b zero} one}}
```

```
{{cons two} zero} ⇒ {fun {b} {{b two} zero}}
```

Implementing Pairs

```
cons def = {fun {x} {fun {y}
              {fun {b} {{b x} y}}}}
```

Can you write a program that takes a pair and returns the first part?

Can you write a program that takes a pair and returns the rest?

```
first def = {fun {p} {p true}}
```

```
rest def = {fun {p} {p false}}
```

Example:

```
{first {{cons zero} one}} ⇒ {first {fun {b} {{b zero} one}}}  
⇒ {{fun {b} {{b zero} one}} true}  
⇒ {{true zero} one}  
⇒ zero
```

Implementing Arithmetic

```
zero def = {fun {f} {fun {x} x}}
```

```
one def = {fun {f} {fun {x} {f x}}}
```

```
two def = {fun {f} {fun {x} {f {f x}}}}
```

Can you write a program that takes a number and adds one?

```
add1 def = {fun {n}
            {fun {g} {fun {y}
                      {g {{n g} y}}}}} }
```

Example:

```
{add1 zero} ⇒ {fun {g} {fun {y}
                {g {{zero g} y}}}}
= {fun {g} {fun {y}
  {g {{{fun {f} {fun {x} x}} g} y}}}}
⇔ {fun {g} {fun {y}
  {g y}}}
= one
```

Implementing Arithmetic

Can you write a program that takes a number and adds two?

```
add2 def = { fun { n } { add1 { add1 n } } }
```

Implementing Arithmetic

Can you write a program that takes a number and adds three?

```
add3 def = { fun {n} { add1 { add1 { add1 n } } } }
```

Implementing Arithmetic

```
zero def = {fun {f} {fun {x} x}}
```

```
one def = {fun {f} {fun {x} {f x}}}
```

```
two def = {fun {f} {fun {x} {f {f x}}}}
```

Can you write a program that takes two numbers and adds them?

```
add def = {fun {n} {fun {m} {{n add1} m}}}
```

... because a number n applies some function n times to an argument

Implementing Arithmetic

```
zero def = {fun {f} {fun {x} x}}
```

```
one def = {fun {f} {fun {x} {f x}}}
```

```
two def = {fun {f} {fun {x} {f {f x}}}}
```

Can you write a program that takes two numbers and multiplies them?

```
mult def = {fun {n} {fun {m} {{n {add m}} zero}}}
```

... because adding number m to zero n times produces $n \times m$

Implementing Arithmetic

Can you write a program that tests for zero?

```
iszero def = {fun {n} {{n {fun {x} false}} true}}
```

because applying `{fun {x} false}` zero times to `true` produces `true`, and applying it any other number of times produces `false`

Implementing Arithmetic

Can you write a program that takes a number and produces one less?

```
shift def = {fun {p}
             {{cons {rest p}} {add1 {rest p}}}}
```

```
sub1 def = {fun {n}
            {first
             {{n shift} {{cons zero} zero}}}}
```

And then subtraction is obvious...

Implementing Factorial

```
mk-rec def = {fun {body}
              {{fun {fX} {fX fX}}
               {fun {fX}
                 {{fun {f} {body f}}
                  {fun {x} {{fX fX} x}}}}}}}
```

Can you write a program that computes factorial?

```
{mk-rec
 {fun {fac}
   {fun {n}
     {{{iszero n}
      one}
     {{mult n} {fac {sub1 n}}}}}}}}
```

... and when you can write factorial, you can probably write anything.